

Table 1 Commonly used hydrolysis and hydrolysis under microwave irradiation of compounds **1–3**.

Starting materials	Commonly used hydrolysis ^a				Hydrolysis in a microwave field ^b			
	Conditions	Time/h	Product	Yield (%)	Conditions	Time/h	Product	Yield (%)
1	5.5 ml of 33% HBr in AcOH	48	4	70	5.0 ml of 25% H ₂ SO ₄	0.5	4	95
2	5.1 ml of 97% H ₂ SO ₄	100	5	90	5.0 ml of 25% H ₂ SO ₄	0.5	5	90
3	5.0 ml of 97% H ₂ SO ₄	70	5	75	5.0 ml of 25% H ₂ SO ₄	0.5	6	80

^a See footnote †. ^b See footnote ‡.

References

- 1 E. J. Richman and T. J. Atkins, *J. Am. Chem. Soc.*, 1974, **96**, 2268.
- 2 R. A. Abramovich, *Org. Prep. Proced. Int.*, 1991, **23**, 685.
- 3 A. G. Whittaker and V. M. P. Mingos, *J. Microwave Power and Electromagnetic Energy*, 1994, **29**, 195.
- 4 K. D. Raner, C. R. Strauss and R. W. Trainor, *J. Org. Chem.*, 1995, **60**, 2456.
- 5 D. D. Dishino, E. J. Delaney, J. E. Emswiler, E. T. Gaughan, J. S. Prasad, S. K. Srivastava and M. F. Tweedle, *Inorg. Chem.*, 1991, **30**, 1265.
- 6 D. I. Weisblat, B. J. Magerlein and D. R. Myers, *J. Am. Chem. Soc.*, 1953, **75**, 3630.

Received: 2nd September 1998; Com. 8/07873D